



SSB-SC AMPLITUDE MODULATION DEMODULATION TRAINER

MODEL - COM103N

This trainer has been designed with a view to provide practical & experimental Knowledge of Single sideband Suppressed carrier Amplitude Modulation /Demodulation technique on a SINGLE P.C.B.



SPECIFICATIONS

1. Power supply requirement : 230V AC, 50 Hz.
2. Built in IC based power supply.
3. On Board AF Modulating signal generator - Sine wave
Frequency Range : 1KHz to 10KHz
Amplitude : 0 to 3 Vpp.
4. On Board RF carrier signal generator.
Frequency Range : 400KHz to 500KHz.
Amplitude : 0 to 10 Vpp.
5. On Board Band Pass Filter : 452-458 KHz Bandwidth
6. Modulator Type : Filter & Phase shift Method.
7. Demodulator Type : Product detector with Low Pass Filter -Cut off Freq. 3.4 KHz.
8. All parts are soldered on single PCB of size 15" x 12" with complete circuit diagram screen-printed.
9. Standard Accessories :
 1. A Training Manual.
 2. Connecting Patch cords.

EXPERIMENTS

1. To generate SSB-SC AM signal using Filter & Phase shift Method
2. To demodulate SSB-SC signal using Product detector (i.e. coherent detection).
3. To see the effect on SSB-SC AM modulated output by varying the amplitude and frequency of modulating signal.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-