



FM STEREO TRAINER

MODEL - RDM200

This trainer has been designed with a view to provide theoretical and practical knowledge of FM stereo on SINGLE PCB.



SPECIFICATIONS

1. Construction	:	Superheterodyne
2. Tuning Range	:	88MHz to 108MHz
3. Inter Mediate Frequency	:	10.7MHz
4. Pilot Frequency	:	19KHz
5. Circuit Block	:	1. FM Detector 2. Stereo Detector 3. Stereo Pre-amplifier 4. Audio Power amplifier
6. Tuning	:	With variable capacitor (Gang) Dial marking on board.
7. Receiver Media	:	Telescopic Antenna
8. Amplifier	:	Class B Amplifier.
9. Audio output	:	(10W + 10W) 20 watts.
10. Speaker	:	8 ohms (2 Nos.)
11. Switch Fault	:	4 Nos.
12. Power supply	:	220V \pm 10% 50Hz.
13. Test Points	:	17 Nos.
14. Fuse	:	350mA
15. Inter connection	:	2mm Banana socket

In keeping view of SIGMA policy of continuous development and improvement, the Specifications may be changed without prior notice or obligation.

Sigma Trainers and Kits
E-113, Jai Ambe Nagar,
Near Udgam School,
Thaltej,
AHMEDABAD - 380054.
INDIA.

Phone(O): +91-79-26852427/ 26850829
Phone(F): +91-79-26767512/ 26767648
Fax : +91-79-26840290/ 26840290
Mobile : +91-9824001168
Email : sales@sigmatrainers.com
: sigmatrainers@sify.com
Web : www.sigmatrainers.com

Dealer:-